

# PFT39XX

## Optical Module



### Features

- Optical fiber interface type :LC
- Wide-range temperature application: -40°C ~85°C

### Specifications

Single-mode					
DHU40080	PFT3910	155M	20km	1310/1550nm	Single fiber bi-directional transmission
DHU40085	PFT3920	155M	20km	1550/1310nm	Single fiber bi-directional transmission
DHU40090	PFT3960	1.25G	20km	1310/1550nm	Single fiber bi-directional transmission
DHU40095	PFT3970	1.25G	20km	1550/1310nm	Single fiber bi-directional transmission
Mult-mode					
DHU40100	PFT3900	155M	2KM	850nm	Double fiber
DHU40105	PFT3950	1.25G	500m	850nm	Double fiber

\*Design and specifications are subject to change without notice.

© 2014 Dahua Technology Co., Ltd.



**seadan**  
security & electronics



VIC Unit 7, 170 Forster Road, Mt Waverley VIC 3149  
NSW Unit 5, 142 James Ruse Drive, Parramatta NSW 2150  
QLD 15-19 Hudson Road, Albion QLD 4010  
WA Unit 4, 200 Balcatta Road, Balcatta WA 6021  
ACT Unit 2, 157-161 Gladstone Street, Fyshwick ACT 2609

You're in very secure company

1300 366 851 | [seadan@seadan.com.au](mailto:seadan@seadan.com.au)

20170123